

## ATR-2612 1/2HPf DC ATOMS GARAGE DOOR OPENER Residential Door/Opener Applications



Solid Tube Rail: For Easy Installation



Three-Button Remote  
MM-318-3



Wall Console  
WB-350



Safety Beam Sensor  
ID-001



1 Piece Solid Rail  
(Chain/Belt)

## PERFORMANCE



### Built-in LED

No light bulb to replace as the lifetime LED is built-in to the opener.



### DC Motor

Ensures extremely quiet and powerful operation.



### Battery Backup Compatible

The backup battery with built-in LED allows you to operate your garage door opener during the power outage.



### Diagnostic Display

LED Display shows current status during programming and system error.

## CONNECTIVITY



### SkylinkNet Compatible

Compatible with SkylinkNet Internet Hub (sold separately) and Smartphone App.



### Monitor Door Status

Receives Push Notification on your smartphone when garage door opener is activated.



### Operate Door Remotely with SkylinkNet App

Remotely open and close the garage door.



### Alarm System & Home Automation

SkylinkNet Internet Hub can be used as an alarm system and home automation gateway.

## SAFETY AND SECURITY



### Rolling Code

Encrypted code is generated with every remote activation.



### Passcode Protected Remote Control

Enable the passcode feature to unlock the remote control. (Only for MM-318 3 buttons)



### Tamper Proof Trolley

Tamper-Proof trolley design provides peace of mind and added security to prevent forceable entry.



### Automatic Door Close Timer

Programmable timer to close the door automatically.



### Visual / Audio Alert

Flashing light and beeping alert when the door is about to close on Automatic Door Close Timer Mode.

# Optional Accessories



Wireless Wall Console    Wireless Safety Sensors    SkylinkNet Smart Phone Control    Backup Battery    Keyless Entry System    Keychain / Visor Remotes    Plug-in ON/OFF Control    Screw-in Dimmer

## STANDARD SPECIFICATION

### DIMENSIONS

- Installed Length:
  - 7' Belt: 124" Chain: 122"
  - 8' Belt: 138" Chain: 136"
  - 10' Belt: 162" Chain: 160"
- Maximum Lifting weight:
  - 600N: 60lbs; 800N: 90lbs
- Maximum Door Opening:
  - 7' max 7'6"
  - 8' max 8'6"
  - 10' max 10'6"
- Min. Headroom Clearance Required:
  - Belt: 2" Chain: 2"

### MM-REMOTE CONTROL

- Rolling Code Technology
- Operating Range: 300' (Open Area)
- Operating Temperature: -22F to 150F
- Battery: 3-Volt Lithium
- Frequency: 318 MHz

### CARTONS

- Number of Cartons: 2
- Carton 1: Dimensions and Contents:
  - 18 3/4" x 6 1/4" x 9 3/4"
  - Garage Door Opener Head
  - PB-001, Push Button (ATR-2611) / WB-350, Wall Console (ATR-2612)
  - MM-318-1, 1x One-Button (ATR-2611) / MM-318-2, 1x Two-Button (ATR-2612)
  - Remote Control
  - Photo-eye Safety reversing system
  - Instruction/Maintenance manual
- Carton 2: Dimensions and Contents:
  - 7' Rail, 117" x 4" x 4.1"
  - 8' Rail, 130" x 4" x 4.1"
  - 10' Rail, 153" x 4" x 4.1"

Assembled Solid Rectangular Tube Rail with pre-wrapped chain or belt and attached front pulley.

### CONVENIENCE / SAFETY

- Auto Force:
  - Down travel safety reversing sensor.
  - Up travel safety stop sensor.
- Emergency/ Quick Release
- Automatic Trolley Reconnect
- Photo-eye; Beam Obstructed
- Lights on; Door Open/ Close
- In-Car Remote Compatible
- Wall control or Remote activation during door travel.
  - Stop Door for Ventilation
- SkylinkNet Compatible- Smartphone Control
- The MM- Remote will only transmit the signal for 3 seconds to prevent battery drain in case the button is accidentally held down.

## ELECTRICAL SPECIFICATION

### POWER

- Voltage: 120V AC, 60Hz
- Operation Rating: 96W
- Current Rating: 0.75A, Maximum 0.9A
- UL Listings: Yes (Conforms to UL STD. 325)
- Length of Line Cord: 5' (3-prong)

### LIGHTING

- Built-in LED
- Maximum Wattage: 12W
- LED is equivalent to 72 watt tungsten light bulb
- Length of Light Delay: 3 Minutes
- Type of Light Delay: Solid-State

## MECHANICAL SPECIFICATION

### MOTOR

- 24V DC Motor, 600N, 1/2HPf equivalent
- RPM: 1,625
- Thermal Protection: Automatic
- Lubrication: Permanent

### DRIVE MECHANISM

- Drive Means: Full Reinforced Drive Belt or Heavy Duty Chain.
- Reduction Means: Gear 16:1
- Door Linkage: Adjustable Door Arm

### ADJUSTMENTS

- Auto Force
- Electronic Limit Settings

### TRAVEL RATE

Approximately 6" per Seconds

### SHIPPING WEIGHTS

- Head: 10lbs
- Belt Rail: 7' 12lbs, 8' 13lbs, 10' 15lbs
- Chain Rail: 7' 14lbs, 8' 15lbs, 10' 18lbs

### MATERIALS

- Chassis: Steel
- Chassis Cover: Plastic
- Rail: Rolled Steel
- Trolley: Plastic

### WARRANTY

- 8 Year Motor Warranty
- 1 Year Parts and Accessories Warranty
- Lifetime Belt Warranty